壳体材料：ABS或PC
材料特性：抗冲击性、耐热性、耐低温性、耐化学药品性及电气性能优良、表面光泽性好等特点
认　　证：CE、ROHS
防护等级：IP65
用　　途：适用于室内、室外电气、通信、消防设备、钢铁冶炼，石油化工，电子、电力，铁路，建筑工地，采矿场，机场，宾馆，船舶、大型工厂、沿海工厂、卸货码头设备、污废水处理设施、环境公害设施等。
安装方式：1. 内部安装：盒子内部有供线路板或DIN轨道元件安装的凸台，及自带的铜接线螺母（每只防水盒内部都配有最少二个以上的很常规的M4的铜螺母）
2. 外部安装：可通过盒体底部的安装孔直接固定于墙面（可通过盒子的四个角，直接用螺丝或钉子固定在墙上或板子上。）
进出线孔：防水盒可以随意跟据客户的使用要求在上面开孔，（开孔位置及开孔大小都可以按照客户指定要求加工。）开孔后可以装有配套的防水夹紧接头，达到防水最佳效果。

Body material: ABS or PC
Material characteristics: Impact, heat, low temperature and chemical resistance, excellent electrical performance and surface gloss, etc.
Certificates: CE, ROHS
Protection grade: IP65
Application: Suitable for indoor and outdoor electric, communication, fire fighting apparatus, iron and steel smelting, petrochemical industry, electron, power system, railway, building, mine, air and sea port, hotel, ship, works, waste water treatment equipment, environmental equipment and so on.
Installation: 1,Inside: There are the installation holes in the base for circuit board or din rail(More than 2 pcs of M4 brass nuts have been in each box).
2,Outside: The products can be directly fixed on the wall or other flat boards with screws or nails via the screw holes in the base.
Outlet hole: Holes can be opened on the box as customers' requirements, and installing cable gland can bring with better waterproof performance.



型号 Model Code	毛重(KG) G. Weight	净重(KG) N. Weight	装箱数(只) Qty/Carton	外箱尺寸(cm) Carton Dimenstion
RFB–GT 300×200×160	12.9	11.4	8	60×46×32
RFB–GT 300×200×180	13.4	11.9	8	64.5×40.5×54
RFB–GT 300×300×180	13.8	12.3	6	61.5×34×56.5
RFB–GT 400×300×180	17.0	15.5	6	66×41×56.5
RFB–GT 500×400×200	13.5	12.0	3	51×44×63
RFB–GT 600×400×220	17.5	16.0	3	61.5×41×68.5