SHANGHAI NEWTREND ELECTRIC CO., LTD.
No. 618 North Huting Road | 201615 | Shanghai | China
Tel / WhatsApp: +86-18019187010 | sales@sntelec.com | www.sntelec.com

NFG250A

DC relay



Series product photograph. Nameplate and configuration depend on the selected model.

Contactor Model	NFG250A
Rated Control Current	250A at 450V DC-1
Coil Voltage	DC12V / DC24V
Contacts	1NO
Contact Operating Voltage Range	12-1000 V DC; see load-life conditions

NewTrend NFG250A DC Relay

250A at 450V DC-1 · Normally open main contact


Main contact form	one normal open
Contact working voltage (V (DC))	12–1000
Rated control capacity	250A 450V (DC-1)
Rated short-time withstand current and duration	250A 1200s
Additional short-time withstand condition	400A 300S
contact voltage drop (mV)	≤ 80 @ 100A current
Action time (including contact bounce) (ms)	≤25
release time (ms)	≤12
Contact bounce time (ms)	≤6
Maximum breaking current (only once on/off)	2500A; 100V
Transform the electrical life of the load (non-polar, purely resistive load) (time)	250A, 450V / 5000
Additional load-life condition	250A, 750V / 1500
Additional load-life condition	250A, 1000V / 1000
Auxiliary contact (optional) (contact form)	/ / one normal open
Contact load rating	2A/30V (DC), 3A/125V (AC)
Minimum value of contact load	100mA/8V
insulation resistance (MΩ)	100 (under 500V (DC) conditions)
Withstand Voltage (V (AC))	3500V (AC) 50 Hz/60 Hz (leakage current ≤ 1mA) 1000V (AC) 50Hz/60Hz (between auxiliary contacts)
Operating Temperature (°C)	-40–+85
Operating Humidity	5%–90%RH
altitude (m)	4000
Shock, 11ms, 1/2 sine wave, peak value (G)	20
Vibration, sine wave, 80-2000Hz, peak value (G)	20
Rated working duty	Continuous working duty
Weight (approximately) (g)	380
Installation method	arbitrary

Coil specifications


Working voltage of coil (V (DC))	12 / 24
Maximum coil voltage (V (DC))	36 / 36
Maximum surge current of coil (A)	3.8 / 3.8
Maximum surge time (ms)	≤110 / ≤110
Coil maintenance power (W)	≤5.0 / ≤5.0
Pick up voltage (VDC)	≤9 / ≤9
Release voltage (VDC)	≤7 / ≤7
Coil polarity	Red line (positive), black line (negative)

NewTrend NFG250A DC Relay


Connection and mounting drawings



1）NFG250A



2）NFG250AS



Supplementary technical sheet compiled from the exact manufacturer web product data.