





M、PG、G、NPT 型波纹管快速接头

- 螺纹规格：公制牙 M、德制牙 PG，英制牙 G，美制牙 NPT。
- 材料：由 UL 认可尼龙 PA66 制成。
- 工作温度：静态 -40~100℃，瞬时热阻高达 120℃；动态 -20~80℃，瞬时热阻高达 100℃。
- 特点：特殊夹紧爪之设计，平紧浪管抗拉力强，超快速拔插装卸，提高安装效率。
- 颜色：黑色，灰色，以及特殊颜色，可按要求定做。
- 备注：特殊尺寸和型号，请与我们联系。

适配软管 Accommodated Pipes	螺牙型号 Thread	型号 Item No.	螺纹外径 (mm) Thread O.D B1	螺纹长度 (mm) Thread Length B2	主体长度 (mm) Joint Length B3
AD10.0	G1/4	D10.0-G1/4	13.1	8.5	23
AD13.0	G3/8	D13.0-G3/8	16.6	10	25
AD15.8	G3/8	D15.8-G3/8	16.6	12.5	28
	G1/2	D15.8-G1/2	20.9	12.5	28
AD18.5	G1/2	D18.5-G1/2	20.9	12.5	29
AD21.2	G1/2	D21.2-G1/2	20.9	13	32
	G3/4	D21.2-G3/4	26.4	13	32
AD25.0	G3/4	D25.0-G3/4	26.4	13	33
AD28.5	G3/4	D28.5-G3/4	26.4	13	35
AD34.5	G1	D34.5-G1	33.2	14	37
AD42.5	G1-1/4	D42.5-G1-1/4	41.9	15	39
AD54.5	G1-1/2	D54.5-G1-1/2	48	16	39
	G2	D54.5-G2	60	16	39

M, PG, G, NPT Type Quick Connector For Fiexible Pipes

- Thread spec.: Mctric, PG, G, NPT.
- Material: Of UL approved nylon PA66
- Working temperature:-40℃ to 100℃ in static state, instantaneous heat resistanceup to 120℃ ;-20℃ to 80℃ in dynamic state.instantancous heat resistance up to 100℃ centigrade.
- Characteristics: The claws of excellent design, to provide a fast & safe commection with the tubing ang to get anexvellent result strength to be the best balanced performers for cable protection system.
- Color: Black, grey as well as special colors that can be designed at request.
- Note: Special size and type, please contant us.