





M、PG、G、NPT 型波纹管快速接头

- 螺纹规格：公制牙 M、德制牙 PG，英制牙 G，美制牙 NPT。
- 材料：由 UL 认可尼龙 PA66 制成。
- 工作温度：静态 -40~100℃，瞬时热阻高达 120℃；动态 -20~80℃，瞬时热阻高达 100℃。
- 特点：特殊夹紧爪之设计，平紧浪管抗拉力强，超快速拔插装卸，提高安装效率。
- 颜色：黑色，灰色，以及特殊颜色，可按要求定做。
- 备注：特殊尺寸和型号，请与我们联系。

适配软管 Accommodated Pipes	螺牙型号 Thread	型号 Item No.	螺纹外径 (mm) Thread O.D B1	螺纹长度 (mm) Thread Length B2	主体长度 (mm) Joint Length B3
AD10.0	M12×1.5	D10.0-M12	12	8	23
AD13.0	M12×1.5	D13.0-M12	12	8	25
	M16×1.5	D13.0-M16	16	10	25
	M18×1.5	D13.0-M18	18	10	25
AD15.8	M16×1.5	D15.8-M16	16	10	28
	M18×1.5	D15.8-M18	18	10	28
	M20×1.5	D15.8-M20	20	10	28
AD18.5	M20×1.5	D18.5-M20	20	10	29
AD25.0	M25×1.5	D25.0-M25	25	10	33
AD34.5	M32×1.5	D34.5-M32	32	15	37
	M40×1.5	D34.5-M40	40	15	37
AD42.5	M40×1.5	D42.5-M40	40	15	39

M, PG, G, NPT Type Quick Connector For Fiexible Pipes

- Thread spec.: Mctric, PG, G, NPT.
- Material: Of UL approved nylon PA66
- Working temperature:-40℃ to 100℃ in static state, instantaneous heat resistanceup to 120℃ ;-20℃ to 80℃ in dynamic state.instantancous heat resistance up to 100℃ centigrade.
- Characteristics: The claws of excellent design, to provide a fast & safe commection with the tubing ang to get anexvellent result strength to be the best balanced performers for cable protection system.
- Color: Black, grey as well as special colors that can be designed at request.
- Note: Special size and type, please contant us.