



M、PG、G、NPT 型波纹管快速接头

- 螺纹规格 : 公制牙 M、德制牙 PG，英制牙 G，美制牙 NPT。
- 材料 : 由 UL 认可尼龙 PA66 制成。
- 工作温度 : 静态 -40~100℃，瞬时热阻高达 120℃ ; 动态 -20~80℃，瞬时热阻高达 100℃。
- 特点 : 特殊夹紧爪之设计，平紧浪管抗拉力强，超快速拔插装卸，提高安装效率。
- 颜色 : 黑色，灰色，以及特殊颜色，可按要求定做。
- 备注 : 特殊尺寸和型号，请与我们联系。

适配软管 Accommodated Pipes	螺牙型号 Thread	型号 Item No.	螺纹外径 (mm) Thread O.D B1	螺纹长度 (mm) Thread Length B2	主体长度 (mm) Joint Length B3
AD10.0	PG7	D10.0-PG7	12.5	11.5	23
AD13.0	PG9	D13.0-PG9	15	11.5	25
AD15.8	PG11	D15.8-PG11	18.6	12	28
AD18.5	PG13.5	D18.5-PG13.5	20.4	12	29
AD21.2	PG16	D21.2-PG16	22.5	13	32
AD25.0	PG21	D25.0-PG21	28.3	13	33
AD28.5	PG21	D28.5-PG21	28.3	13	35
AD34.5	PG29	D34.5-PG29	37	15	37
AD42.5	PG36	D42.5-PG36	47	15	39
AD54.5	PG42	D54.5-PG42	54	16	39
	PG48	D54.5-PG48	59.3	16	39

M, PG, G, NPT Type Quick Connector For Fiexible Pipes

- Thread spec.: Mctric, PG, G, NPT.
- Material: Of UL approved nylon PA66
- Working temperature:-40℃ to 100℃ in static state, instantaneous heat resistanceup to 120℃ ;-20℃ to 80℃ in dynamic state.instantancous heat resistance up to 100℃ centigrade.
- Characteristics: The claws of excellent design, to provide a fast & safe commection with the tubing ang to get anexvellent result strength to be the best balanced performers for cable protection system.
- Color: Black, grey as well as special colors that can be designed at request.
- Note: Special size and type, please contant us.