



M、PG 型高抗拉波纹管接头

- 螺纹规格 : 公制牙 M、德制牙 PG，英制牙 G，美制牙 NPT。
- 材料 :A、C、E、F 部分由 UL 认可尼龙 PA66 制成，B 部分由丁腈橡胶 (NBR) 制成。
- 工作温度 : 静态 -40-100℃，瞬时热阻高达 120℃ ; 动态 -20-80℃，瞬时热阻高达 100。
- 特点 : 这种高性能抗拉型浪管接头适用于不同材料和不同硬度浪管。
- 颜色 : 黑色 , 灰色 , 以及特殊颜色 , 可按要求设计。
- 备注 : 特殊尺寸和型号，请与我们联系。

M, PG Type Superb Pullout Strength Conduit Fitting

- Thread spec.: Metric, PG, G, NPT.
- Material: Parts A,C,E,F are made of UL approved nylon PA66, parts B aremade of nitrile butadiene rubber (NBR).
- Working temperature:-40℃ to 100℃ in static state, instantaneous heat resistanceup to 120℃ ;-20℃ to 80℃ in dynamic state. instantaneous heat resistance up to 100 centigrade.
- Characteristics: This high performance tensile wave tube joint is suitable for different materials and different hardness wave tubes.
- Color: Black, grey as well as special colors that can be designed at request.
- Note: Special size and type, please contant us.

适配软管 Accommodated Pipes	型号 Item No.	螺牙型号 Thread	螺纹外径 (mm) Thread O.D C1	螺纹长度 (mm) Thread Length C2	幅体最小通径 (mm) F1
AD10	L-M12-10	M12×1.5	12	9	8
AD13	L-M16-13	M16×1.5	16	15	11.1
	L-M18-13	M18×1.5	18	9	10.7
AD15.8	L-M16-15.8	M16×1.5	16	15	11
	L-M18-15.8	M18×1.5	18	15	11
	L-M20-15.8	M20×1.5	20	15	14.5
AD18.5	L-M20-18.5	M20×1.5	20	15	14.5
AD21.2	L-M20-21.5	M20×1.5	20	15	14.5
	L-M25-21.5	M25×1.5	25	15	19
AD25	L-M25-25	M25×1.5	25	15	19.2
AD28.5	L-M25-28.5	M25×1.5	25	15	19.2
AD34.5	L-M32-34.5	M32×1.5	32	15	26.3
AD42.5	L-M40-42.5	M40×1.5	40	15	34.1
AD54.5	L-M50-54.5	M50×1.5	50	20	41.4
	L-M63-54.5	M63×1.5	63	20	53.6
AD10	L-PG7-10	PG7	12.5	8.5	8.5
AD13	L-PG9-13	PG9	15	10	10.4
AD15.8	L-PG11-15.8	PG11	18.6	10	13.7
	L-PG13.5-15.8	PG13.5	20.4	10	15.1
AD18.5	L-PG13.5-18.5	PG13.5	20.4	10	15.1
AD21.2	L-PG16-21.2	PG16	22.5	10	16.1
AD25	L-PG21-25	PG21	28.3	12	19.2
AD28.5	L-PG21-28.5	PG21	28.3	12	23.2
AD34.5	L-PG29-34.5	PG29	37	12	28.1
AD42.5	L-PG36-42.5	PG36	47	15	37.3
AD54.5	L-PG42-54.5	PG42	54	20	41.4
	L-PG48-54.5	PG48	59.3	20	51.8