




## M 型尼龙电缆防水接头（分体）

- 螺纹规格：公制牙 M。
- 材料：A、C、E、F 部分由 UL 认可尼龙 PA66 制成，B、D 部分由丁腈橡胶 (NBR) 制成。
- 工作温度：静态 -40~100℃，瞬时热阻高达 120℃；动态 -20-80℃，瞬时热阻高达 100℃。
- 特点：夹紧圈和橡胶件的特殊设计、夹持电缆的范围大，超强的抗拉伸力，防水性，防尘性，耐盐、酸、碱、醇、脂、通用溶剂的能力强。
- 防护等级：IP68。
- 颜色：黑色、灰色，以及特殊颜色，可按要求设计。
- 备注：特殊尺寸和型号，请与我们联系。

## M Type Nylon Cable Glands (Divided Structure)

- Thread spec.: Metric.
- Material: Parts A,C,E,F are made of UL approved nylon PA66, parts B and D are made of nitrile butadiene rubber (NBR).
- Working temperature:-40℃ to 100℃ in static state, instantaneous heat resistance up to 120℃ ;-20℃ to 80℃ in dynamic state. instantaneous heat resistance up to 100℃ centigrade.
- Characteristics: Special design of clamping die and rubber part, large range in clamping cable, ultra-strong stretching resistance, waterproof, dustproof, and high ability to resist salt, acid, alkali, alcohol, grease and general solvent.
- Protectiongrade: IP68.
- Color: Black,grey as well as special colors that can be designed at request.
- Note:Special size and type, please contant us.

| 螺牙型号 Thread | 型号 Item No. | 适用电缆 Cable range | 螺纹外径 (mm) Thread O.D C1 | 螺纹长度 (mm) Thread Length C2 | 扳手直径 (mm) Spanner size A & CF |
|---|---|---|---|---|---|
| M12×1.5 | 12A-8 | 4-8 | 12 | 9 | 17/19 |
| | 12A-5.5 | 3-5.5 | 12 | 9 | 17/19 |
| M16×1.5 | 16AS-8 | 4-8 | 16 | 9 | 22/19 |
| | 16AS-5.5 | 3-5.5 | 16 | 9 | 22/19 |
| | 16ASL-8 | 4-8 | 16 | 15 | 22/19 |
| | 16ASL-5.5 | 3-5.5 | 16 | 15 | 22/19 |
| | 16A-10 | 6-10 | 16 | 9 | 24/22 |
| | 16A-7 | 4-7 | 16 | 9 | 24/22 |
| | 16AL-10 | 6-10 | 16 | 15 | 24/22 |
| | 16AL-7 | 4-7 | 16 | 15 | 24/22 |
| M18×1.5 | 18A-10 | 6-10 | 18 | 9 | 24/22 |
| | 18A-7 | 4-7 | 18 | 9 | 24/22 |
| | 18AL-10 | 6-10 | 18 | 15 | 24/22 |
| | 18AL-7 | 4-7 | 18 | 15 | 24/22 |
| M20×1.5 | 20AS-12 | 7-12 | 20 | 10 | 27/24 |
| | 20AS-9 | 5-9 | 20 | 10 | 27/24 |
| | 20ASL-12 | 7-12 | 20 | 15 | 27/24 |
| | 20ASL-9 | 5-9 | 20 | 15 | 27/24 |
| | 20A-14 | 8.5-14 | 20 | 10 | 27/24 |
| | 20A-11 | 7-11 | 20 | 10 | 27/24 |
| | 20AL-14 | 8.5-14 | 20 | 15 | 27/24 |
| | 20AL-11 | 7-11 | 20 | 15 | 27/24 |
| M25×1.5 | 25A-18 | 12-18 | 25 | 12 | 33/33 |
| | 25A-16 | 11-16 | 25 | 12 | 33/33 |
| | 25AL-18 | 12-18 | 25 | 15 | 33/33 |
| | 25AL-16 | 11-16 | 25 | 15 | 33/33 |
| M32×1.5 | 32A-25 | 18-25 | 32 | 12 | 41/41 |
| | 32A-22 | 16-22 | 32 | 12 | 41/41 |