



M 型耐扭式尼龙电缆接头

- 螺纹规格：公制牙 M，德制牙 PG，英制牙 G，美制牙 NPT。
- 材料：A、C、F 部分由 UL 认可尼龙 PA66 制成，B、D 部分由丁腈橡胶 (NBR) 制成。
- 工作温度：静态 -40-100℃，瞬时热阻高达 120℃；动态 -20-80℃，瞬时热阻高达 100℃。
- 特点：夹紧圈和橡胶件的特殊设计，夹持电缆的范围大，超强的抗拉伸力，防水性，防尘性，耐盐、酸、碱、醇、脂、通用溶剂的能力强。
- 防护等级：IP68。
- 颜色：黑色，灰色，以及特殊颜色，可按要求设计。
- 备注：特殊尺寸和型号，请与我们联系。

M Type Spiral Nylon Cable Gland

- Thread spec.: Metric, PG, G, NPT.
- Material: Parts A,C,F are made of UL approved nylon PA66, parts B and Dare made of nitrile butadiene rubber (NBR).
- Working temperature:-40℃ to 100℃ in static state, instantaneous heat resistanceup to 120℃ ;-20℃ to 80℃ in dynamic state. instantaneous heat resistance up to 100℃ centigrade.
- Characteristics: Special design of clamping die and rubber part, large range in clamping cable,ultra-strong stretching resistance, waterproof, dustproof, and high ability to resist salt, acid, alkali, alcohol, grease and general solvent.
- Protection grade: IP68.
- Color: Black, grey as well as special colors that can be designed at request.
- Note: Special size and type, please contant us.

螺牙型号 Thread	型号 Item No.	适用电缆 Cable range	螺纹外径 (mm) Thread O.D C1	螺纹长度 (mm) Thread Length C2	扳手直径 (mm) Spanner size A & CF
M12×1.5	12-8	4-8	12	9	17/19
	12-5.5	3-5.5	12	9	17/19
M16×1.5	16S-8	4-8	16	9	22/19
	16S-5.5	3-5.5	16	9	22/19
	16SL-8	4-8	16	15	22/19
	16SL-5.5	3-5.5	16	15	22/19
	16-10	6-10	16	9	24/22
	16-7	4-7	16	9	24/22
	16L-10	6-10	16	15	24/22
	16L-7	4-7	16	15	24/22
M18×1.5	18-10	6-10	18	9	24/22
	18-7	4-7	18	9	24/22
	18L-10	6-10	18	15	24/22
	18L-7	4-7	18	15	24/22
M20×1.5	20S-12	7-12	20	10	27/24
	20S-9	5-9	20	10	27/24
	20SL-12	7-12	20	15	27/24
	20SL-9	5-9	20	15	27/24
	20-14	8.5-14	20	10	27/27
	20-11	7-11	20	10	27/27
	20L-14	8.5-14	20	15	27/27
	20L-11	7-11	20	15	27/27
M25×1.5	25-18	12-18	25	12	33/33
	25-16	11-16	25	12	33/33
	25L-18	12-18	25	15	33/33
	25L-16	11-16	25	15	33/33
M32×1.5	32-25	18-25	32	12	41/41
	32-22	16-22	32	12	41/41