





M 型尼龙电缆防水接头（连体）

- 螺纹规格：公制牙 M。
- 材料：A、C、F 部分由 UL 认可尼龙 PA66 制成，B、D 部分由丁腈橡胶 (NBR) 制成。
- 工作温度：静态 -40 ~100℃，瞬时热阻高达 120℃；动态 -20-80℃，瞬时热阻高达 100℃。
- 特点：夹紧圈和橡胶件的特殊设计，夹持电缆的范围大，超强的抗拉伸力，防水性，防尘性，耐盐、酸、碱、醇、脂、通用溶剂的能力强。
- 防护等级：IP68。
- 颜色：黑色，灰色，以及特殊颜色，可按要求设计。
- 备注：特殊尺寸和型号，请与我们联系。

M Type Nylon Cable Glands (United Structure)

- Thread spec.: Metric.
- Material: Parts A,C, F are made of UL approved nylon PA66,parts B and D are made of nitrile butadiene rubber (NBR).
- Working temperature; -40℃ to 100℃ in static state, instantaneous heat resistance up to 120℃; -20℃ to 80℃ in dynamic state. instantaneous heat resistance up to 100℃ centigrade.
- Characteristics: Special design of clamping die and rubber part, large range in clamping cable, ultra-strong stretching resistance, waterproof, dustproof, and highability to resist salt, acid, alkali, alcohol, grease and general solvent.
- Protection grade: IP68.
- Color: Black,grey as well as special colors that can be designed at request.
- Note:Special size and type, please contant us.

螺牙型号 Thread	型号 Item No.	适用电缆 Cable range	螺纹外径 (mm) Thread O.D C1	螺纹长度 (mm) Thread Length C2	扳手直径 (mm) Spanner size A & CF
M8×1.25	8B-4.5	2.5-4.5	8	7.5	13/12
	8B-2.5	1-2.5	8	7.5	13/12
M10×1.5	10B-6	2-6	10	8	15/13
	10B-3	1.5-3	10	8	15/13
M12×1.5	12BS-6.5	3-6.5	12	8	17/16
	12BS-5.5	3-5.5	12	8	17/16
	12BSL-6.5	3-6.5	12	15	17/16
	12BSL-5.5	3-5.5	12	15	17/16
	12B-8	4-8	12	9	17/19
	12B-5.5	3-5.5	12	9	17/19
M16×1.5	16BS-8	4-8	16	9	22/19
	16BS-5.5	3-5.5	16	9	22/19
	16BSL-8	4-8	16	15	22/19
	16BSL-5.5	3-5.5	16	15	22/19
	16B-10	6-10	16	9	24/22
	16B-7	4-7	16	9	24/22
	16BL-10	6-10	16	15	24/22
	16BL-7	4-7	16	15	24/22
M18×1.5	18B-10	6-10	18	9	24/22
	18B-7	4-7	18	9	24/22
	18BL-10	6-10	18	15	24/22
	18BL-7	4-7	18	15	24/22
M20×1.5	20BS-12	7-12	20	10	27/24
	20BS-9	5-9	20	10	27/24
	20BSL-12	7-12	20	15	27/24
	20BSL-9	5-9	20	15	27/24
	20B-14	8.5-14	20	10	27/27
	20B-11	7-11	20	10	27/27
	20BL-14	8.5-14	20	15	27/27
	20BL-11	7-11	20	15	27/27
M25×1.5	25B-18	12-18	25	12	33/33
	25B-16	11-16	25	12	33/33
	25BL-18	12-18	25	15	33/33
	25BL-16	11-16	25	15	33/33
M32×1.5	32B-25	18-25	32	12	41/41
	32B-22	16-22	32	12	41/41
M40×1.5	40B-32	24-32	40	15	52/52
	40B-26	21-26	40	15	52/52
M50×1.5	50B-39	31-39	50	20	60/62
	50B-32	26-32	50	20	60/62
M63×1.5	63B-44	32-44	63	20	74/68
	63B-38	30-38	63	20	74/68