



PG、NPT、G 型耐扭式尼龙电缆接头

- 螺纹规格 : 公制牙 M, 德制牙 PG，英制牙 G, 美制牙 NPT。
- 材料 :A、C、F 部分由 UL 认可尼龙 PA66 制成，B、D 部分由丁腈橡胶 (NBR) 制成。
- 工作温度 : 静态 -40 ~100℃，瞬时热阻高达 120℃ ; 动态 -20-80℃，瞬时热阻高达 100℃。
- 特点 : 夹紧圈和橡胶件的特殊设计，夹持电缆的范围大，超强的抗拉伸力，防水性，防尘性，耐盐、酸、碱、醇、脂、通用溶剂的能力强。
- 防护等级 : IP68
- 颜色 : 黑色，灰色，以及特殊颜色，可按要求设计。
- 备注 : 特殊尺寸和型号，请与我们联系。

PG, NPT, G Type Spiral Nylon Cable Gland

- Thread spec.: Metric, PG,G, NPT.
- Material: Parts A,C, F are made of UL approved nylon PA66, parts B and Dare made of nitrile butadiene rubber (NBR).
- Working temperature:-40℃ to 100℃ in static state, instantaneous heat resistanceup to 120℃ ;-20℃ to 80℃ in dynamic state. instantaneous heat resistance up to 100℃ centigrade.
- Characteristics: Special design of clamping die and rubber part, large rangein clamping cable,ultra-strong stretching resistance, waterproof, dustproof,and high ability to resist salt, acid, alkali, alcohol, grease and general solvent.
- Protection grade: IP68.
- Color: Black,grey as well as special colors that can be designed at request.
- Note: Special size and type, please contant us.

螺牙型号 Thread	型号 Item No.	适用电缆 Cable range	螺纹外径 (mm) Thread O.D C1	螺纹长度 (mm) Thread Length C2	扳手直径 (mm) Spanner size A& CF
NPT 3/8	PT 3/8-10	6-10	16.662	10	22
	PT 3/8-7	4-7	16.662	10	22
NPT 1/2	PT 1/2-12	7-12	20.955	10	24
	PT 1/2-9	5-9	20.955	10	24
NPT 3/4	PT 3/4-18	12-18	26.441	15	33
	PT 3/4-16	11-16	26.441	15	33
G 3/8	3/8-10	6-10	16.662	10	24/22
	3/8-7	4-7	16.662	10	24/22
G 1/2	1/2-12	7-12	20.955	10	27/24
	1/2-9	5-9	20.955	10	27/24
G 3/4	3/4-18	12-18	26.441	12	35/33
	3/4-16	11-16	26.441	12	35/33