



PG型尼龙电缆防水接头（分体）

- 螺纹规格：德制牙 PG。
- 材　料：A、C、E、F 部分由 UL 认可尼龙 PA66 制成，B、D 部分由丁腈橡胶（NBR）制成。
- 工作温度：静态 -40-100℃，瞬时热阻高达 120℃；动态 -20-80℃，瞬时热阻高达 100℃。
- 特点：夹紧圈和橡胶件的特殊设计，夹持电缆的范围大，超强的抗拉伸力，防水性，防尘性，耐盐、酸、碱、醇、脂、通用溶剂的能力强。
- 防护等级：IP68
- 颜色：黑色，灰色，以及特殊颜色，可按要求设计。
- 备注：特殊尺寸和型号，请与我们联系。

PG Type Nylon Cable Glands (Divided Structure)

- Thread spec.: PG.
- Material: Parts A, C, E, F are made of UL approved nylon PA66, parts B and D are made of nitrile butadiene rubber (NBR).
- Working temperature: -40℃ to 100℃ in static state, instantaneous heat resistance up to 120℃; -20℃ to 80℃ in dynamic state. instantaneous heat resistance up to 100℃ centigrade.
- Characteristics: Special design of clamping die and rubber part, large range in clamping cable, ultra-strong stretching resistance, waterproof, dustproof, and high ability to resist salt, acid, alkali, alcohol, grease and general solvent.
- Protection grade: IP68.
- Color: Black, grey as well as special colors that can be designed at request.
- Note: Special size and type,please contant us.

螺牙型号 Thread	型号 Item No.	适用电缆 Cable range	螺纹外径 (mm) Thread O.D C1	螺纹长度 (mm) Thread Length C2	扳手直径 (mm) Spanner size A & CF
PG7	G7A-8	4-8	12.5	9	17/19
	G7A-5.5	3-5.5	12.5	9	17/19
PG9	G9A-8	4-8	15	9	22/19
	G9A-5.5	3-5.5	15	9	22/19
PG11	G11A-10	6-10	18.6	9	24/22
	G11A-7	4-7	18.6	9	24/22
PG13.5	G13.5A-12	7-12	20.4	10	27/24
	G13.5A-9	5-9	20.4	10	27/24
PG16	G16A-14	8.5-14	22.5	10	30/37
	G16A-11	7-11	22.5	10	30/27
PG21	G21A-18	12-18	28.3	12	35/33
	G21A-16	11-16	28.3	12	35/33
PG29	G29A-25	18-25	37	12	45/42
	G29A-22	16-22	37	12	45/42
PG36	G36A-31	24-31	47	15	56/52
	G36A-26	21-26	47	15	56/52
PG42	G42A-39	31-39	54	20	65/62
	G42A-32	26-32	54	20	65/62
PG48	G48A-44	32-44	59.3	20	70/68
	G48A-38	30-38	59.3	20	70/68
PG63	G63B-42	42-53	70	26	82/75