
Main performance and characteristics of the product

Use PC plastic and plate screw crimp technology, rated voltage AC660V, connecting wire interface 0.75-35mm2, 25mm type C rail mounting. It is widely used.



Main technical data

Type	Dimension mm			Wire section mm^2	Current A	Bolt	Terminal type
	B	H	D				
JH9-1.5	32	31.5	8	0.75-1.0-1.5	17.5	M3	TU1-1/3,1.5/3,TO1-1/3,1.5/3
JH9-1.5ZG		32.5	2				
JH9-2.5	40	33.5	11	1.0-1.5-2.5	24	M4	TU1-1/4,TO1-1/4 TU1-1.5/4,TO1-1.5/4 TU1-2.5/4,TO1-2.5/4
JH9-2.5Z		35	12				
JH9-2.5ZG		33.5	2				
JH9-6	43	36.5	14	2.5-4-6	41	M5	TU1-2.5/5,TO1-2.5/5 TU1-4/5,TO1-4/5 TU1-6/4,TO1-6/4
JH9-6Z		38	15				
JH9-6ZG		36.5	2				
JH9-10	50	38.5	16.5	4-6-10	57	M6	TO1-4/6,TO1-6/6, TO1-10/6
JH9-10Z		40	17.5				
JH9-10ZG		38.5	2	10-16-25	101	M6	TO1-10/6,TO1-16/6, TO1-25/6
JH9-25	60	41.5	18.5				
JH9-25Z		43	19.5				
JH9-25ZG		41.5	2				



