

Main performance and characteristics

Use thermosetting plastic, high-current safety factor is more reliable, using plate screw crimp technology, rated voltage AC600V, rated current of the conductive sheet total of seven levels 60,100,150,200,300,400,600A, connecting wire interface 10-300mm2, equipped with OT, UT ends use more solid and reliable, it can be used as various types of electrical devices with high current terminal.







Main technical data

Type	Conductor section mm2	Voltage & Current	Terminals
TC-603	4-6-10	600V	3
TC-604		60A	4
TC-1003	10-16-25	600V	3
TC-1004		100A	4
TC-1503	25-35-50	600V	3
TC-1504		150A	4
TC-2003	35-50-70	600V	3
TC-2004		200A	4
TC-3003	70-95-150	600V	3
TC-3004		300A	4
TC-4003	150-185-240	600V	3
TC-4004		400A	4
TC-6003	185-240-300	600V	3
TC-6004		600A	4

Type	Dimensions mm								
	L	L1	A	B	C	D	E	F	G
TC-603	28.5	86.5	42.7	38	25.5	31	15	17	M6
TC-604	28.5	115	42.7	38	25.5	31	15	17	M6
TC-1003	34.5	113.5	55.2	46.5	28	36.3	17.3	22.5	M6
TC-1004	34.5	137.5	55.2	46.5	28	36.3	17.3	22.5	M6
TC-1503	38.5	115	67	57.2	30.5	40	19.8	25.3	M8
TC-1504	38.5	153	67	57.2	30.5	40	19.8	25.3	M8
TC-2003	44.5	133	72.1	63	34	44.4	23	28.3	M8
TC-2004	44.5	177	72.1	63	34	44.4	23	28.3	M8
TC-3003	55	164	89.4	78	47.5	50.6	27	30	M10
TC-3004	55	218	89.4	78	47.5	50.6	27	30	M10
TC-4003	55	164	89.4	78	47.5	50.6	27	36	M10
TC-4004	55	218	89.4	78	47.5	50.6	27	36	M10
TC-6003	-	205	70	-	-	70	-	-	-
TC-6004	-	275	70	-	-	70	-	-	-