Main performance and characteristics of the product


UK series terminal blocks use the box type screw press design according to IEC60947-1, GB14048 standards. It is used for AC 50/60Hz 660V or DC 440V system. The wire cross-section range is 0.75-150mm2, also suitable for untreated round type copper conductors.

1.1Reasonable installation design, it can be installed on both G type and TH type rail.

1.2Full types of small sizes, can connect bigger size wires. For 50mm2 and below size copper press board and copper screws are used while bigger size than 50mm2 products use steel press board and steel screws.

1.3Very strong combination function.







Main technical data

Type	Rigidity wire mm2	Flexable wire mm2	Rated current (A)	Rated voltage (V)	Dimension		
					A	B	C
UK2.5B	0.2-4	0.2-2.5	32	690	42	42.5	6.2
UK3N	0.2-4	0.2-2.5	32	800	47	42.5	5.2
UK5N	0.2-6	0.2-4	41	800	47	42.5	6.5
UK6N	0.2-10	0.2-6	57	800	47	42.5	8.2
UK10N	0.5-16	0.5-10	76	800	47	42.5	10.2
UK16N	2.5-25	4-16	101	800	54	42.5	12.2
UK35	10-35	10-35	150	1000	51	55	15.2
UKH50	16-50	25-50	150	1000	83.5	70.5	20
UKH95	25-95	35-95	232	1000	97.5	83	25
UK150	35-150	50-150	309	1000	118.5	100	31

Type	Rigidity wire mm2	Flexable wire mm2	Rated current (A)	Rated voltage (V)	Dimension		
					A	B	C
USLKG2.5	0.2-4	0.2-2.5	32	800	42	42.5	6.2
USLKG3	0.2-4	0.2-2.5	32	800	47	42.5	5.2
USLKG5	0.2-4	0.2-4	34	800	47	42.5	6.2
USLKG6	0.2-10	0.2-6	57	800	47	42.5	8.2
USLKG10	0.5-16	0.5-10	76	800	47	42.5	10.2
USLKG16	2.5-25	4-16	101	800	47	42.5	12.2
USLKG35	10-35	10-35	125	800	51	55	15.2
USLKG50	16-50	25-50	150	800	83.5	70.5	20.5