Air Conditioning Disconnects



UOF2030 30A Fusible

Features


- NEMA 3R outdoor enclosures offered in metallic and non-metallic versions.
- Easy-to-remove high-strength protective shield for easier wiring and mounting.
- Easy-to-remove front cover (no screws or fasteners to remove).
- 1-inch knockouts on the bottom, back and side of unit Copper-rated line and load lugs that are easily accessible.
- Ample wiring space for mounting with a stud gun (single keyhole, two or three-point mounting).
- Fused devices are service entrance rated.
- Padlockable door provision for safety and reduction of tampering.
- Metallic enclosures are bottom entry and exit only.
- Non-metallic enclosures have knockouts and a hub provision for top access.
- Non-metallic enclosures have a single unit door and protective shield for installer convenience.
- Non-metallic enclosures are durable and provide excellent resistance to climate changes.
- Factory-installed tamper-resistant / weather-resistant receptacles are available as an option on some products.



UOF2060 60A Fusible

Specification

Product Number	Main Ampere Rating	HP Rating		Wire Size Range Cu/Al 60℃ or 75℃	Outline Dimensions		
	Metallic / Plastic	120V	240V		H	W	D
UON2030 30A Fusible	30AMP, 240VAC 1 PHASE, 3 WIRE	STD.0.5 MAX.2	STD.0.5 MAX.3	#14-3	225	138.4	76.7
UOF2060 60A Fusible	60AMP, 240VAC 1 PHASE, 3 WIRE	STD.0.5 MAX.3	STD.0.5 MAX.10	#14-3	225	138.4	76.7
UON2060 60A Non-fusible	60AMP, 240VAC 1 PHASE, 3 WIRE	-	STD.3 MAX.10	#14-3	185.7	138.4	76.7



UON2060 60A Non-fusible

Outline Dimensions

